



Citation Manufacturing Co., Inc.

71 E. Eckerson Road • Spring Valley, NY 10977 • Ph/Fax 845-425-6868



ARCHITECTS AND ENGINEERS SPECIFICATION

MODEL S201 Series-Plenum Mounted Speaker shall contain a four inch diameter high efficiency speaker. The speaker shall be contained in a metal canister with dimensions of 6 inch diameter x 8 inches high, that will be supported by a #16 single jackchain, 3 feet long with an S-hook that will allow the speaker canister to be mounted into the ceiling plenum. The unit shall contain a continuously variable volume control to adjust the volume level to 90 dB(A). The volume control shall be mounted to a printed circuit board along with three two pin headers that will allow interconnection between speakers and the noise generators source. In case of 25/70 volts to 8 ohms transformer hook-up, the specified tap, .5, .75, 1.25, 2.5, 5 watts shall be attached at the factory to the printed circuit board.

The MODEL S201-Series Plenum Mounted Speaker is available as follows:

S201-08	8 ohms
S201-25	25 volts
S201-70	70 volts

The S201 Series Plenum Mounted Speaker may be used with the M101- Series Noise Generator, Power Amplifiers with 25/70 volts output, Graphic Equalizers for Sound Masking, paging or background music applications.